


130 GLASS DRILL BIT



DRIVE



D Ø mm	D Ø "	L1 mm	d Ø mm		EAN 4016707	
3,0	1/8	58	3,0	20	010019	130 000 030
4,0	5/32	58	3,5	20	010026	130 000 040
5,0	3/16	58	4,0	20	010033	130 000 050
5,5	7/32	58	4,0	20	010200	130 000 055
6,0	15/64	58	5,0	20	010040	130 000 060
7,0	9/32	78	5,0	20	010057	130 000 070
8,0	5/16	78	6,0	20	010064	130 000 080
9,0	11/32	98	6,0	20	010071	130 000 090
10,0	3/8	98	6,0	20	010088	130 000 100
12,0	15/32	98	8,0	20	010095	130 000 120

EXECUTION

- Specially ground carbide tip
- Zinc-plated surface
- Thinned cross cutting edges provide precise drilling of pilot holes

FOR USE IN



APPLICATION

- In all rotary and percussion drilling machines
- In machines for mechanical processing
- Only for rotary use
- In materials up to scratch hardness of 8

PACKAGING



[162]

Comments

- Set a low speed
- Cool sufficiently with water, turpentine, vinegar or paraffin
- Regrind frequently when drilling in hard materials

GLASS DRILL BIT

The classic drilling tool for glass machining. Drills precise and exact holes in sensitive and hard materials. The specially ground cutting edges allow a careful drilling process. The tool life can be considerably prolonged by means of regrinding. During drilling process sufficient cooling and slow rotation speed is needed.

